

# 5300 Contempo Specification Sheet

# **SAFETY EYEWEAR**

### **PRODUCT DESCRIPTION:**

Bouton 5300 Contempo Goggles, indirect vent, full polycarbonate frame, anti-scratch lenses, elastic braid strap with adjustable buckle.

- · Universal goggle design;
- · Indirect ventilation, channels across top and bottom for air flow;
- Meets ANSI Z87.1+ High Impact Requirements;
- · Frame splits at nose for comfort fit;
- · Side recesses to accept eyewear temples;
- · Pliable one-piece frame;

#### Applications:

Used for general manufacturing and anywhere eye protection is needed, for work and home projects.

# **TECHNICAL DATA:**

Base Curve Lens: 4

Packaging: 1 unit per polybag, 50 units per case

Case Weight: 6 lbs / 2.7 kg

Country of Origin/Harmonization Code: Taiwan/9004.90.0000 Frame Design: Full polycarbonate single lens, non-toxic PVC frame

 $Strap: 1" \times 19"$  Elastic Braid with slide buckles and twist lock strap adaptor

Ventilation: Indirect, top and bottom, liquid channels across top for protection against liquid splash, dust and liquid drops.

Color: Clear Blue Transparent to prevent yellowing




Polycarbonate lenses block 99.9% of the sun's ultraviolet rays. This ultraviolet protection has already been incorporated within the lens material when the lenses are being produced.

Item #	Lens Material	Lens Color	Lens Coating	<u>Frame</u>	UPC #	UPC # Case
251-5300-000	Polycarbonate, 0.080 CT	Clear	Anti-scratch	Light blue transparent	01616314106292	02616314106291
251-5300-400	Polycarbonate, 0.080 CT	Clear	Anti-scratch, anti-fog	Light blue transparent	01616314106308	02616314106307
251-5300-402	Polycarbonate, 0.080 CT	Smoke	Anti-scratch, anti-fog	Light blue transparent	01616314106315	02616314106314

# **DIMENSIONS:**

Size Available	One size	
Overall Length (mm) - A	90.0	
(in)	3.5	
Lens Height (mm) - B	83.0	
(in)	3.27	
Overall Width (mm) - C	186.0	
(in)	7.32	



This document is the property of PIP and the information contained herein is proprietary to PIP.