



SPECIFICATION SHEET

16-3400R

SEAMLESS KNIT GLOVES

G-Tek™ CR, Hi-Vis Orange HPPE/Glass 13 Gauge Seamless Shell, Double Dipped Black Micro-Surface Nitrile Coated Palm and Fingers.

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling
- Construction

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	HPPE/glass shell with nitrile coated palm and fingers
CONSTRUCTION	Seamless Knit
COLOR	Hi-Vis Orange & Black
SIZES	S - XXL
PACKAGING	1 pair per bag, 12 pairs per dozen, 12 dozen per case
CASE	22" x 12.6" x 14" / 56cm x 32cm x 36cm
COO	China
HARM CODE	6116.10.6500
MFG CERT.	ISO9001:2000 Certified

BARCODES

ITEM	DOZEN	CASE	CASE WEIGHT
16-3400R/S	01616314130754	02616314130753	23.5 lbs. / 10.7 kgs
16-3400R/M	01616314130747	02616314130746	24.6 lbs. / 11.2 kgs
16-3400R/L	01616314130730	02616314130739	27 lbs. / 12.2 kgs
16-3400R/XL	01616314130761	02616314130760	28 lbs. / 12.7 kgs
16-3400R/XXL	01616314130778	02616314130777	30.2 lbs. / 13.7 kgs

PERFORMANCE PROPERTIES

ASTM F1790-04: 1214 grams +/- 10%; ANSI Cut Level 3.

Abrasion	0	1	2	3	4
Cut	0	1	2	3	4
Tear	0	1	2	3	4
Puncture	0	1	2	3	4



DIMENSIONS (in/cm)

	SIZE	S	M	L	XL	XXL
A	Over Length	9.3/23.7	9.7/24.7	10.1/25.7	10.5/26.6	10.7/27.2
B	Palm Width	3.6/9.2	3.9/9.9	4.1/10.4	4.2/10.6	4.4/11.3
H	Hem Color	Red	Yellow	Brown	Black	Sky Blue

