



SPECIFICATION SHEET

16-820

SEAMLESS KNIT GLOVES

G-Tek™ CR, Salt & Pepper HPPE/Glass 13 Gauge Seamless Outer Shell, Acrylic Inner Liner, Double Dipped Black & Blue Latex Micro-Surface Coated, 3/4 Dipped.

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling
- Construction
- Freezer work

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	HPPE/glass outer shell/acrylic inner shell with latex coated palm and fingers
CONSTRUCTION	Seamless Knit
COLOR	Black & White
SIZES	S - XXL
PACKAGING	1 pair per bag, 12 pairs per dozen, 12 dozen per case
CASE	31.5" x 11.8" x 20.9" / 80cm x 30cm x 53cm
COO	China
HARM CODE	6116.10.6500
MFG CERT.	ISO9001:2000 Certified



DIMENSIONS (in/cm)

	SIZE	S	M	L	XL	XXL
A	Over Length	9.8/25	10.2/26	10.4/26.5	10.8/27.5	11/28
B	Palm Width	4.1/10.3	4.2/10.7	4.3/11	4.5/11.3	4.6/11.7
H	Hem Color	Red	Yellow	Brown	Black	Sky Blue

BARCODES

ITEM	DOZEN	CASE	CASE WEIGHT
16-820/S	01616314131096	02616314131095	40.9 lbs. / 18.6 kgs
16-820/M	01616314131089	02616314131088	41.6 lbs. / 18.9 kgs
16-820/L	01616314131072	02616314131071	44.5 lbs. / 20.2 kgs
16-820/XL	01616314131102	02616314131101	47.8lbs. / 21.7 kgs
16-820/XXL	01616314131119	02616314131118	51.5 lbs. / 23.4 kgs

PERFORMANCE PROPERTIES

ASTM F1790-04: 1133 grams +/- 10%; ANSI Cut Level 3.

Abrasion	0	1	2	3	4
Cut	0	1	2	3	4 5
Tear	0	1	2	3	4
Puncture	0	1	2	3	4

