

SPECIFICATION SHEET 17-D350

ANSICUT LEVEL

UNCOATED GLOVES MADE WITH DYNEEMA®

- 100% Dyneema®, 7 gauge, heavy weight
- Seamless construction provides comfort without sacrificing dexterity
- Can be used as glove liners
- Color coded hems for easy size identification
- Made from component materials that comply with Federal Regulations for food contact 21CFR, 170-199
- Dyneema® is a brand of polyethylene fibers that are 10 to 15 times stronger than steel, more durable than polyester and a strength that is 40% greater than aramid fiber

APPLICATIONS

- Food processing
- Can also be used as glove liners

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40° C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Hang dry or tumble dry low

TECHNICAL DATA

| MATERIAL | Dyneema® | | |
|---------------------|--|--|--|
| CONSTRUCTION | 7 gauge | | |
| COLOR | □ White | | |
| CUFF STYLE | Continuous knit | | |
| SIZES | XS - XL | | |
| PACKAGING | 12 pairs per dozen, 6 dozen per case | | |
| CASE | 20.0" x 13.0" x 16.0" / 50.8cm x 33cm x 40.6cm | | |
| CASE WEIGHT (XS-XL) | 16.5 lbs / 7.5 kg | | |
| C00 | USA | | |

CUT RESISTANCE PROPERTIES

- Method ASTM F1790-04
- 1250 grams

ANSI/ISEA 105-2000 Level 3 Cut Resistance


BARCODES

| ITEM | BAG | DOZEN | CASE |
|--------------|-----|----------------|----------------|
| 🗆 17-D350/XL | | 01616314036927 | 02616314036927 |
| 🗆 17-D350/L | | 01616314036897 | 02616314036897 |
| 🗆 17-D350/M | | 01616314036903 | 02616314036903 |
| 🗆 17-D350/S | | 01616314036910 | 02616314036910 |
| 🗆 17-D350/XS | | 01616314036934 | 02616314036934 |



DIMENSIONS (in/cm)

| | XS | | М | | XL |
|---|------------|------------|-------------|--------------|-------------|
| Α | 7.0 / 17.8 | 8.5 / 21.6 | 10.0 / 25.4 | 10.25 / 26.0 | 10.5 / 26.7 |
| В | 3.9 / 9.9 | 4.0 / 10.2 | 4.5 / 11.4 | 4.5 / 11.4 | 4.5 / 11.4 |
| н | Blue | White | Red | Yellow | Grey |



PROTECTIVE INDUSTRIAL PRODUCTS www.pipusa.com • sales@pipusa.com • (800) 262-5755 • (518) 864-0144 fax