

17-SDG325 Specification Sheet

UNCOATED GLOVES MADE WITH DYNEEMA®

PRODUCT DESCRIPTION:

Dyneema®, Seamless knit with spun Dyneema®/nylon and Nuaramid®, elastic cuff, 7 gauge, medium weight, gray, EN cut level 3.

- · Styles are washable, improving their longevity.
- Seamless knit construction provides comfort without sacrificing dexterity.
- · Color coded hems provide easy size identification.
- Gloves are made from component materials which comply with Federal regulations for food contact 21CFR 170-199.

Applications:

Ideal for automotive repair and maintenance, assembly, glass handling, canning, and food processing. Can also be used as glove liners.

TECHNICAL DATA:

Material: Spun Dyneema®/nylon and Nuaramid®

Color: Gray

Cuff Style: Continuous knit, elastic cuff

Available Sizes: S - XL

Packaging: 1 pair per bag, 12 pairs per dozen, 6 dozen per case Case Dimensions (cm): $50.8 \times 33 \times 40.6$ / (in): $20 \times 13 \times 16$ Case Weight: (S) 10.5 lbs / 4.7 kg (M) 12 lbs / 5.4 kg

(L) 10.8 lbs / 4.9 kg (XL) 12.3 lbs / 5.6 kg

Country of Origin/Harmonization Code: USA/6116.93.8800

Laundering Instructions:

Recommend washing gloves in slightly warm water not exceeding 40° C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low to medium heat.

Dyneema*


DIMENSIONS:

Size Available	<u>s</u>	<u>M</u>	<u>L</u>	XL
Over Length (cm) - A	21.6	25.4	26.0	26.7
(in)	8.5	10.0	10.25	10.5
Palm Width (cm) - B	10.2	11.4	11.4	11.4
(in)	4.0	4.5	4.5	4.5
Hem Color	White	Red	Yellow	Green

CUT RESISTANCE PROPERTIES:

- Method ASTM F1790-04
- 916 GRAMS
- ANSI/ISEA 105-2000 Level 2 Cut Resistance
- EN388 Level 3 Cut Resistance

BARCODE #	BARCODE # DOZEN	
17-SDG325/XL	01616314059154	02616314059153
17-SDG325/L	01616314058362	02616314058361
17-SDG325/M	01616314059147	02616314059146
17-SDG325/S	01616314059437	02616314059436



This document is the property of PIP and the information contained herein is proprietary to PIP.