

939-EF350 Specification Sheet

E-FLARE WARNING BEACON

PRODUCT DESCRIPTION:

e-Flare warning beacon, flashing 1-color, standard 4 LED intensity, low battery indicator; amber or red beacon.

- Intensely Bright Can be seen for over 1/2 mile away without night vision, point fixation and distance judgement problems.
- Portable Unit is less than 6" tall and weighs less than one pound.
 Includes lanyard for easy transport.
- . Simple To Use Twist the lens to turn on or off.
- Durable Waterproof and dustproof, plus e-Flare will survive a 3-foot drop onto a concrete surface.
- Double the Safety Provide safety by ensuring maximum 360° visibility. No risk of fire or explosion, and there are no toxic fumes or residue.
- Versatile Easily attaches to belts, clothing, vehicles, traffic cones or signs.

Applications:

Ideal for police, firefighters, airports, traffic control, parking valets, construction sites and other public safety applications. Designed for use in Class 1, Division 2/ Zone 2 hazardous areas.

TECHNICAL DATA:

Color: Lime yellow body; amber or red LED.

Beam brightness: 15,000 - 25,000 millicandela

Max beam conspicuity: Between horizontal and 10 degrees above

horizontal

Flash rate: 165-185 flashes per minute

Batteries: 4 alkaline AA cells (For maximum performance, Duracell or

Everready are recommended)

Battery life: Up to 30 hours at full brightness

Packaging: 1 per bag, 12 per case

Weight per unit (including batteries): $0.6\ \mbox{lbs}\,/\,0.27\ \mbox{kg}$

Case Weight: 8 lbs / 3.6 kg


Country of Origin/Harmonization Code: China / 8530.80.0000





DIMENSIONS:

Size Available	One size
Height-including base (cm) – A (in)	14.5 5.7
Diameter (cm) - B	4.0
(in)	1.6



This document is the property of PIP and the information contained herein is proprietary to PIP.